Product data sheet

DOWNTOWN NO TRIM Ø215 03.0461/TC-TEL/2X26W

FLOS









Luminaires for embedded installation indoor with fluorescent lamps and of halogenuro metalist. Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.

Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	26 W	Socket	Gx24Q-3
Lamp flux	1800 lm	LOR	38%
Luminous efficacy	53 lm/W	Total flux	1366 lm
CCT	4000 K	Total power	26 W
CBI	80		



2 x Compact fluorescent lamp

Nominal lamp power	26 W	Socket	Gx24Q-3
Lamp flux	1800 lm	LOR	38%
Luminous efficacy	53 lm/W	Total flux	1366 lm
CCT	3000 K	Total power	26 W
CDI	9.4		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.36 in Diameter: 7.99 in

Adjustability

Fixed

Electric

System power: 26 W

Protection

IP: 23