Product data sheet

INDUSTRIAL AND WAREHOUSE LIGHTING

V1-I0-72582-03GOD-6702440 IRON GL 0,5 M 24W 4000K TEMPERED GLASS DALI LAMBERT

VARTON



IP 67 IK 08

Linear lamp in an anodized aluminum housing for fire-hazardous areas with low ceilings, impact-resistant tempered glass, a wide range of lengths and capacities. The CLEANPRO version is a dirt-repellent (oleophobic) coating on the glass. Installation: Suspended (cable suspension is ordered separately) and overhead, using stainless steel brackets (included in the delivery package). The suspensions snap into a groove located along the entire length of the lamp, which allows you to adjust the position of the already mounted lamp. Application: Lighting of rooms with low ceilings - industrial premises, food industry workshops, livestock complexes, clean rooms, industrial workshops, warehouses, transport infrastructure, fire-hazardous areas Input voltage (AC, 50Hz): 198...264 AC frequency: 50 Input voltage (DC): 190...280 Flicker: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK08 Power factor: 0,95 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/iron-gl/iron-gl-0-5-m/svetodiodnyy-svetilnik-varton-ayron-gl-24vt-4000k-0-5m-klass-zashchity-ip67-opalovyy-rasseivatel-zak_1/

Light output 1



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2440 lm	Total flux	2440 lm
Luminous efficacy	102 lm/W	Total power	24 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.83 in
Width: 3.39 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 67
IK: 08