

Product data sheet

NUMINOS DL XL
1004050
SLV




IP
44


IK
02

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 37.4 watts, luminous flux of 3750 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.


Light output 1




1 x LED			
Nominal lamp power	38 W	LOR	100%
Lamp flux	2412 lm	Total flux	2412 lm
Luminous efficacy	62 lm/W	Total power	38.8 W
CCT	3966 K		
CRI	91		



1 x LED			
Nominal lamp power	38 W	LOR	100%
Lamp flux	2708 lm	Total flux	2708 lm
Luminous efficacy	70 lm/W	Total power	38.8 W
CCT	3966 K		
CRI	91		



1 x LED			
Nominal lamp power	38 W	LOR	100%
Lamp flux	3105 lm	Total flux	3105 lm
Luminous efficacy	80 lm/W	Total power	38.9 W
CCT	3966 K		
CRI	91		



1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

40 W
3745 lm
92 lm/W
3966 K
91

LOR
Total flux
Total power

100%
3745 lm
40.6 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in
Width: 6.30 in
Height: 0.33 in
Weight: 0.66 kg

Adjustability

Fixed

Electric

System power: 38.8-40.6 W
Controller: Dimmable 1..10V, DALI

Protection

IP: 44
IK: 02