




Product data sheet

OMEGA LED 1000-840 HF E3
96602042
THORN LIGHTING




A ceiling recessed LED luminaire with a slim 12mm profile. Electronic, fixed output control gear with 3 hour, manual test, LED emergency lighting circuit. Class I electrical, IP44 from below, IP44_IP20 from above, IK02. Body: sheet steel, white (RAL9016). Diffuser: UV-stabilized opal acrylic. Electrical connection via push wire terminal blocks, loop in/loop out possible. Complete with 4000K LED Dimensions: 300 x 300 x 12 mm Total power: 12.3 W Weight: 3.8 kg

Light output 1 (emergency)



1 x General service incandescent lamp			
Nominal lamp power	12 W	LOR	100%
Lamp flux	390 lm	Total flux	390 lm
Luminous efficacy	389964 lm/W	Total power	0 W
CCT	3000 K		
CRI	99		

Light output 2



1 x General service incandescent lamp			
Nominal lamp power	12 W	LOR	100%
Lamp flux	920 lm	Total flux	920 lm
Luminous efficacy	75 lm/W	Total power	12.3 W
CCT	3000 K		
CRI	99		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 11.81 in
Width: 11.81 in
Height: 0.47 in
Weight: 3.8 kg

Design

Color of housing: White

Electric

System power: 12.3 W
Voltage: 220-240 V AC
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20

IK: 02

Designation labels: CE