



Product data sheet

NANOTTICA 1.5FT ABSC 4000/840 1F
100696
TREVOS



absolute control over emitted light thanks to patented nano-optics; variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting; basic beam angle: medium beam (MB); optimal mounting height: 3.5 to 8 m; ON/OFF electronic driver (AC, DC on demand); Body: dark grey ABS (high chemical resistance, UV stability, RAL 7001); Diffuser: clear AC with nano-optics (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: stainless steel + polyamide; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless three-pole terminal block, 3-wire connecting cabling for feed-through installation (1.5 mm² cross-section, 2.5 mm² available on demand); Power: 25,3 W; Luminaire flux: 3680 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK06; Ambient temperature: -25|50 °C; Weight: 2,1 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25.3 W	CRI	80
Total flux	4180 lm	LOR	100%
Luminous efficacy	165 lm/W	ULOR	4%
		Total power	25.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.28 in

Width: 3.86 in

Height: 3.31 in

Adjustability

Fixed

Design

Material impression: Plastic

Color of housing: Silver gray, White

Designer: TREVOS

Electric

System power: 25.3 W

Ballast: ECG

Appliance Class: I

Protection

IP: 66

IK: 06

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...122°F