Product data sheet

+WT20600F LINEAR 2.1 A [3000K 4W 230VAC]
CL21105AF
L&L LUCE&LIGHT



IP 65 IK 06

Bollard for outdoor applications; surface mounted (ground); body in aluminium alloy EN AW 6060, screen in tempered glass; finishes: anthracite, cor-ten, grey; 1 power LED (4W), 1 power LED High Intensity (8,5W); 4W, 8,5W - 230Vac; built in power supply unit; connection box with 1 m cable, H05RN-F 2x0,75 Ø6,3 mm; total delivered lumens: 100 lm (3000K, 4W), 284 lm (3000K, 8,5W); asymmetrical optics; LED colour: white - 2700K, 3000K, 4000K; ingress protection: IP65; impact resistance: IK06; operating temperature: -20°C+45°C; Glow Wire Test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: I; weight 1,60 kg h 120 mm, kg 2,0 h 250 mm, kg 2,7 h 600 mm, kg 3,1 h 800 mm; dimensions 100x100x120/250/600/800 mm; accessories: plate for in-ground installations WT000000, column - height 250 mm WT20250F / WT20250H / WT20250R, column - total height 600 mm WT20600F / WT20600H / WT20600R, column - total height 800 mm WT20800F / WT20800H / WT20800R

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	80
Total flux	100 lm	LOR	100%
Luminous efficacy	25 lm/W	Total power	4 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 23.62 in

Adjustability

Fixed

Electric

System power: 4 W
Appliance Class: I

Protection

IP: 65
IK: 06