



Product data sheet

DEIMOS LED PLUS 400MM 2200 LM 830 CZARNY (20W) RCR DALI CORRIDOR
657207
LENA LIGHTING



657207 DEIMOS LED PLUS 400mm 2200 lm 830 czarny (20W) RCR DALI CORRIDOR Surface-mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED. HIPS base, powder-coated white and black; light, white diffuser made using termoforming method. Simple pawl-based mounting system does not require any additional tools. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	21 W	CRI	80
Total flux	2200 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	21 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.54 in
Diameter: 15.75 in

Adjustability

Fixed

Design

Material impression: Matt, Plastic
Color of housing: White

Glare protection

Glare protection: UGR < 19

Electric

System power: 21 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 40
IK: 02
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F