

# Product data sheet

AVIATO

741882.004.1


RZB



Series: Aviato Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Rotates 356° horizontally and swivels 180° vertically, passive cooling. Reflector: faceted aluminium. LED included, with multi adapter for 230V 3 circuit tracks, ceiling mounted. Anti-reflective safety glass is an accessory and must be ordered separately. Available Colours: silver Type of Installation: Track on ceiling Dimensions: L 208, B 106, H 240 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 3200lm System power: 36W Beam Angle: 24° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A Unified Glare Ratio: 24,5 EEC: A+

---

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	3200 lm	LOR	100%
Luminous efficacy	89 lm/W	Total power	36 W

---

## Mounting mode

Ceiling mounted

Electric

System power: 36 W

## Shape and measurements

Length: 4.17 in

Protection

Width: 8.19 in

IP: 20

Height: 9.45 in

IK: 02

## Adjustability

Rotatable, Tiltable