


# Product data sheet

QUADRANA LIGHT SPACE

311484.002

RZB




IP  
40

IK  
05

Series: Quadrana Light Space Type of Protection: IP 40 Protection Class: I Voltage: 200 - 240 V / 0 Hz, 50 - 60 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: toggles. Diffuser: plastic (PMMA), opal. Front side: transparent, with LED cooling frame: stainless steel, brushed. With Gore-TM Protective Vents membrane valve as standard. With 16 LEDs and electronic constant current supply. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 300, B 300, H 115 Lamp: LED Colour Temperature: blue Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 75lm System power: 23W Beam Angle: 171°/113° Number of fittings B10A: 6 Number of fittings B16A: 13 Number of fittings C10A: 14 Number of fittings C16A: 22 Inrush current: 54A Unified Glare Ratio: 5,6

## Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	23 W	CRI	60
Total flux	75 lm	LOR	100%
Luminous efficacy	3 lm/W	ULOR	68%
		Total power	23 W

## Mounting mode

Wall mounted

## Electric

System power: 23 W

## Shape and measurements

Length: 11.81 in

Width: 11.81 in

Height: 4.53 in

## Protection

IP: 40

IK: 05

## Adjustability

Fixed