


Product data sheet

SUPERLINEA STAND-ALONE 1536 DOWN LED 19.2W RA92 3500K 230V/50HZ IP20 EXTRA WIDE FLOOD 75MA
723-42-DW-20-27-X


EXENIA



IP
20

The new polyspherical or linear fly-eye optics have made it possible to conceive innovative lighting units with absolutely unique size/performance ratios. The Superlinea project aims to make system composition easy and intuitive by offering simple pre-assembled modules, with driver on board, to be connected in sequence with quick couplings and very few additional elements. The configurations offered are divided between: linear modular system in ceiling or suspension mode and simplified stand-alone, ceiling or suspension mode. We have prioritised longitudinal and transverse visual comfort in order to achieve consistently low UGR factors and efficiencies in the region of 140 lumens/W, while maintaining the slim, minimalist design typical of the Exenia style. Each suspended unit is available in single-emission and bi-emission modes

Light output 1



1 x LED

Nominal lamp power	21.5 W	LOR	100%
Lamp flux	2974 lm	ULOR	100%
Luminous efficacy	138 lm/W	Total flux	2974 lm
CCT	3500 K	Total power	21.5 W
CRI	92		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 0.94 in

Width: 60.75 in

Height: 3.35 in

Adjustability

Fixed

Electric

System power: 21.5 W

Protection

IP: 20