


# Product data sheet

MIRL NIV LED3800-830 M625Q WB LDO KA  
42928773  
ZUMTOBEL



Modular LED ceiling-recessed luminaire with lens optic. Total power: 27.4 W, Slave luminaire for DALI control (DALI only) with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 85% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 3620 lm, Luminaire efficacy: 132 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. Symmetric very wide distribution luminaire (wide beam). Light control via square lens optic for glare-free light distribution with ; low dirt sensitivity and simple cleaning; flat sheet steel luminaire housing with enamelled finish in white; installation as height-adjustable luminaire for cut ceiling apertures and modular ceilings with concealed or visible grid system; please order fixing kit separately; Luminaire wired with halogen-free leads; Dimensions: 623 x 623 x 74 mm, weight: 6.84 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.4 W	CRI	80
Total flux	3620 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	27.4 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 24.53 in  
Width: 24.53 in  
Height: 2.91 in  
Weight: 6.8 kg

## Design

Color of housing: White

## Electric

System power: 27.4 W  
Voltage: 220-240 V AC  
Controller: DALI  
Appliance Class: I

## Protection

IP: 40  
Designation labels: CCC, CE, ENEC