Product data sheet


FLEX STRIP OPAL SHAPE DIGITAL 2G - TOP
L6OP70SEG
PROLED (MBN GMBH)



IP 65

Maximum creative freedom with minimum effort? Here we go! Shape makes you want to create surprising applications, sets accents and attracts attention. The DIGITAL version is perfect for exhibition stand construction, event projects and all areas where the effect is the main focus. With the digital controllers (PROLED Pixel Controller; DiGidot Controller and LED CTRL Controller), each segment can be controlled individually. - Each segment can be controlled digitally via UCS1903_800kHz. - Infinite design possibilities for light and luminaire - Combines light and luminaire design in a virtuoso manner - Can be suspended and suspended vertically, horizontally and in almost any shape - Extensive mounting material such as polycarbonate tubes and suspension aids (must be manufactured by PROLED) - 360° light emission. - Dimmable and controllable with suitable PWM dimmers or MULTI power supply units/controllers - For pre-assembled lengths, heat-sealed IP67 end caps and feeds ex works offer an optimum and safe option for equipping the FLEX STRIP OPAL for operation in all environments.

Light output 1



1 x LED RGB

Nominal lamp power	16 W	LOR	100%
Lamp flux	450 lm	Total flux	450 lm
Luminous efficacy	28 lm/W	Total power	16 W
CCT	3000 K		
CRI			

Mounting mode

Pendant

Shape and measurements

Length: 39.37 in
Width: 0.91 in
Height: 0.91 in

Adjustability

Fixed

Electric

System power: 16 W
Controller: Dimmable 1..10V, DMX, DALI
Color adjustable
Appliance Class: III

Protection

IP: 65

Other operating numbers

Ambient temperature range: 14...113°F