



Product data sheet

ETC140-T/E-70/H[A.ASC]
185-2333
WE-EF



IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection. 'No tool' removable gear/reflector tray. Anodised aluminium reflector. Factory fitted, ceramic coated spreader lens. The optional installation blackout is recommended for mounting. To be ordered separately.

Light output 1



| | | | |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 70 W | Socket | G12 |
| Lamp flux | 7300 lm | LOR | 32% |
| Luminous efficacy | 30 lm/W | ULOR | 32% |
| CCT | 3000 K | Total flux | 2302 lm |
| CRI | 85 | Total power | 78 W |

Mounting mode

Floor recessed

Shape and measurements

Height: 12.40 in
Diameter: 11.81 in

Electric

System power: 78 W
Appliance Class: I

Protection

IP: 67