Product data sheet

RECESSED CEILING LUMINAIRE SOLO SLIM OFFICE L1 26W 4050LM C
1022.5534 - SOLO SO CR664 LED4050-840 DIR WH DALI
REGENT



IP 40

Recessed ceiling luminaire Solo Slim Office for false ceilings, with LED, system power: 26 W, standby power 0.5 W, luminous flux of luminaire 4050 lm, colour rendering index CRI > 80, 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 8.9 A, direct light emission, housing in metal, white, without ceiling trim, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0290), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP40, glow wire test 650 °C, this product contains a light source of energy efficiency class B Ø = 664 mm, DAø = 670 mm, ET = 100 mm

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	4050 lm	Total flux	4050 lm
Luminous efficacy	135 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in
Diameter: 26.14 in
Weight: 8.343 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 26 W
Appliance Class: I

Protection

IP: 40