


Product data sheet

STANDARD
50500.009.1
RZB




IP
44

IK
07

Series: Standard Type of Protection: IP 44 Protection Class: II Voltage: - 250 / 0 - 60 Hz Base: plastic, grey. Five cable inlets, one cable inlet with cable grommet. Cover: textured glass, transparent. Protective cage: hinged, steel wire, galvanised. Available Colours: grey Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 176, B 122, H 110 Lamp: 1 x E27 max. 60 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Beam Angle: 90°/90°/62°/90° Unified Glare Ratio: 26,1 EEC: A++ - E

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	15 W	Socket	E27
Lamp flux	970 lm	LOR	72%
Luminous efficacy	46 lm/W	ULOR	17%
CCT	2700 K	Total flux	695 lm
CRI	80	Total power	15 W

Mounting mode

Wall mounted

Shape and measurements

Length: 4.80 in
Width: 6.93 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 15 W

Protection

IP: 44
IK: 07