Product data sheet

DEECOS S MINI TRACK-IN
742252.003.3.76
RZB



IP 20 IK 06

Series: DEECOS S mini track-in LED surface-mounted projector in modern design with no visible cooling ribs. Housing made of die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. With adapter for RZB 3-circuit DALI tracks. Suitable for Track on ceiling, Wall track. DALI track-in converter integrated in the adapter for controlling, switching and dimming.High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: deep black, matt (RAL 9005) Diameter: 87 mm Height: 135 mm Lamp: LED Socket: without socket Colour temperature: 3500K Colour rendering index (CRI): 92 System power: 20 W Rated luminous flux: 2650 lm Beam angle Down: 60° Luminous efficiency: 133 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3500 K
Nominal lamp power	20 W	CRI	90
Total flux	2650 lm	LOR	67%
Luminous efficacy	132 lm/W	ULOR	14%
		Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.31 in
Diameter: 3.43 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Black

Electric

System power: 20 W

Protection

IP: 20
IK: 06