


Product data sheet

MAXOS FUSION LL523X PSD ELD3 EM 1 XLED100S/830 DA25W
LL500X
PHILIPS



Guaranteed performance, thinking ahead Maxos fusion is an adaptable LED trunking system that offers an excellent quality of light while more than halving energy costs compared to fluorescent lamps. For retail applications, a family of linear panels, non-linear modules and a spot portfolio can be smoothly integrated into the track backbone to let your merchandise sparkle and stand out. For industrial applications, the focus is on reducing installation and maintenance cost by using fewer linear panels. With the electrical set-up of up to 13 wires, the freedom to position these fixtures as required and the integration of other services/third-party hardware, the system allows you to reduce ceiling clutter. It can also be easily re-configured to accommodate future lay-out changes. The infrastructure is enabled to integrate sensors for data collection, giving you the opportunity to use insightful granular information to support your business.

Light output 1



1 x LED			
Nominal lamp power	6 W	LOR	100%
Lamp flux	360 lm	Total flux	360 lm
Luminous efficacy	60 lm/W	Total power	6 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 6 W

Shape and measurements

Length: 90.55 in

Width: 2.44 in

Height: 2.17 in