Product data sheet

PAULA V 9.645.2056.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order special pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	100 W	
Lamp flux	10400 lm	
Luminous efficacy	75 lm/W	
CCT	2000 K	
CRI	25	

LOR	83%
Total flux	8643 lm
Total power	115 W



1 x High pressure sodium vapour lamp			
Nominal lamp power	70 W		
Lamp flux	5600 lm		
Luminous efficacy	56 lm/W		
CCT	2000 K		
CRI	25		

LO	OR	83%
Т	otal flux	4654 lm
Т	otal power	83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in Diameter: 28.74 in Electric

System power: 83-115 W

Protection

IP: 55