

# Product data sheet


2X36 W ZONE 2 /ZONE 22 EXPLOSION-PROOF FLUORESCENT LUMINAIRE  
MSEXND236EVG  
MAZINOOR



IP  
65

EXPLOSION PROOF surface mounted luminaire is suitable for using in areas in which an explosive atmosphere is likely to occur in normal operation occasionally. High light efficiency, qualified manufacturing procedure, good function in dusty places, high mechanical resistance, safety and the ease of service are among the greatest advantages of this luminaire. STANDARDS: Manufactured to comply with EN 60598 / BS 4533, CE marked Application: Suitable to use where high efficiency and good mechanical strength is required in places in which an explosive atmosphere is likely to occur in normal operation occasionally. (Zones 1, 21 and 2, 22) such as refineries, power plants, chemical industries, etc

## Light output 1



### 2 x Fluorescent lamp tubular T8

Nominal lamp power	36 W	LOR	79%
Lamp flux	2500 lm	ULOR	13%
Luminous efficacy	55 lm/W	Total flux	3930 lm
CCT	3850 K	Total power	72 W
CRI	79		

## Mounting mode

Ceiling mounted

## Electric

System power: 72 W

## Shape and measurements

Length: 50.00 in

Width: 7.87 in

Height: 4.92 in

## Protection

IP: 65

## Adjustability

Fixed