

# Product data sheet


A55-W1200 LED 5600 840  
GLAMOX



IP  
20

Light source LED 926 mm length LED 4500 - 5800 Lumen out 1226 mm length LED 5600 - 7000 Lumen out Light source information: 3000/4000 Kelvin, CRI 80, CRI 90 on request. 926 mm with CCT on request, MacAdams 3. Lifetime LED: Up to 100.000h Ta25. For precise technical information please see the data sheet on item level. (Use <Find your version> on right hand side) T5 926 mm length Up 2x21/39W Down 1x14/24W 1226 mm length Up 2x28/54W Down 1x14/24W Ballast T5: Electronic ballast (HF) or DALI. LED: DALI Body material & colour Aluminum profile with steel base powder coated Mounting frame in alu-zinc Diffuser up and down in acrylic material resistant to detergents and disinfection liquids. Mounting Surface mounted directly to the wall. Connection 3/5 pole push-in terminal block ready for through wiring. Electrical connection in center of the luminaires as standard, asymmetrical electrical connection is available on request.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	66 W	CRI	80
Total flux	5648 lm	LOR	100%
Luminous efficacy	86 lm/W	ULOR	87%
		Total power	66 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 48.27 in  
Width: 7.52 in  
Height: 3.74 in

## Adjustability

Fixed

## Electric

System power: 66 W

## Protection

IP: 20