Product data sheet

WL STELLA V/06 DA LED (OPTIC 058)
9.601.8117.058-3
LEIPZIGER LEUCHTEN



IP 65

mounting height: 2.50m – 4.00m light standards: for low and medium lighting requirements lamp: incl. 1 x DA+ (2x4) LED module, easy to replace colour temperature: 3,000K warm white or 4,000K neutral white surge protection: 10kV LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming, DALI or CLEVER LIGHT optical system: directed light (multi layer) provided by an computer optimised anti-aging lens technology; dark sky light distribution: street optics, square optics, area optics, cycle path optics luminaire head: made of stainless steel and cap made of aluminium; powder coated wall bracket: made of hot dip galvanised steel with wall shield; powder coated colour: DB 703; other RAL or DB colour without extra cost on request glazing: PMMA RESIST, clear, high-impact wiring: via a plug and socket connector below the luminaire heads installation: to be screwed to the wall accessory: fixing material for the wall installation, cable, back light shield for non-glare on the rear side – to be ordered separately application areas: promenades, parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distributor roads, paths

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	70
Total flux	1950 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	15 W

Mounting mode

Wall mounted

Shape and measurements

Height: 42.52 in
Diameter: 6.69 in
Weight: 16.2 kg

Adjustability

Fixed

Electric

System power: 15 W

Protection

IP: 65