


# Product data sheet

NEO 1 X 11.3W 40° 3000 K  
GH5715.BRMT300EN  
GHIDINI



Series of recessed lighting fixtures. Available in various sizes, they are designed for lighting facades, small, medium and tall trees, shrubs and bushes, columns and other architectural elements in general thanks to a wide range of optics and wattages. The body and diffuser closure ring are constructed of high oxidation resistant aluminum alloy which is subjected to nano-bonderite treatment and finished with texturized polyester powder paint, making the product resistant to atomospheric agents and UV rays, guaranteeing maximum protection over the years. Silicone gaskets ensure maximum sealing in all operating and temperature conditions. The ultra transparent tempered sodium calcium glass diffuser ensures maximum light transmittance and is finished with a silkscreen border. The external finishing frame and screws are in stainless steel. As an alternative to the stainless steel frame, the natural bronze frame is also available. The product is equipped with the Ghidini water-lock system which prevents condensation from the power cable due to the alternating on and off cycles. The product is installed with a polypropylene rough-in housing that prevents the contact of the fixture directly with the ground and allows the necessary space for wiring. The product can be driven over at low speeds (max 15 / kmh) in areas not permitted for traffic. Not suitable for installation in swimming pools or fountains.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	90
Total flux	1378 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	12 W

## Mounting mode

Floor recessed

## Shape and measurements

Height: 0.08 in  
Diameter: 5.31 in

## Adjustability

Fixed

## Electric

System power: 12 W  
Appliance Class: I

## Protection

IP: 68