
Product data sheet

PRIMA 1.2FT PIR PCC 2200/840 COR
107227
TREVOS



resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces; variable suspension spacing ranging from 110 - 370 mm; enable the light to be installed onto suspension fittings left over from previous lighting; optimal mounting height: 3 to 8 m; digitally dimmable. DALI driver with corridor function; Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: translucent PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: stainless steel + polyamide; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless three-pole terminal block; Power: 14,6 W; Luminaire flux: 2190 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|45 °C; Weight: 1,1 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14.6 W	CRI	80
Total flux	2360 lm	LOR	100%
Luminous efficacy	162 lm/W	ULOR	4%
		Total power	14.6 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.21 in
Width: 3.86 in
Height: 3.31 in

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Silver gray, White
Designer: TREVOS

Electric

System power: 14.6 W
Ballast: ECG
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F