Product data sheet


LTH01003001-LINGZHONG-3W-4000K-30°-WH
140042058
OPPLE



IP 20

Housing:plastic; Reflector:polycarbonate with vacuum plating; Mounting ring:plastic,white; Mounting location: Ceiling; 0°-30°vertical tilting angle adjustability; Power:3W; Lamp(s):LED 840; Colour temperature:4000K; Colour rendering:RA82; Total luminous flux of luminaire:150lm, Service life:20,000h at 70% luminous flux; Degree of protection:IP20; Class of protection II; Mains voltage:220V/50Hz; Two fixing clips provided for tool-free installation in ceilings of thickness 1-25 mm; Dimensions:Φ91×49mm; Ceiling cutouts:Φ78mm; Converter:Bulid-in

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	82
Total flux	150 lm	LOR	100%
Luminous efficacy	50 lm/W	Total power	3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.58 in
Width: 3.58 in
Height: 1.93 in
Weight: 0.094 kg

Adjustability

Free

Electric

System power: 3 W
Appliance Class: II

Protection

IP: 20