


Product data sheet

TINY LARGE
05-E147-Z5-CL
LEDSC4



LedsC4 Tiny Large 05-E147-Z5-CLV1 Recessed wall lighting for outdoor use. For frontal lighting and downlighting. Metres of cable included: 2. Structure material: Aluminium. Structure finish: Urban grey. Diffuser material: Glass. Diffuser finish: Sandblasted. UV protection. Warranty: 5 Years. Max. temperature: 50°C. Product net weight (Kg): 0.81 Product length (mm): 60 Product width or diameter (mm): 165 Product height (mm): 38 Product aperture (mm): 2.5 Class 1. Glow wire test: 850. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: BRIDGELUX. Driver brand: HEP. Maximum power of light source: 5.9W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 21.2. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 74. Real lm/W: 9. Voltage / frequency range: 220-240/50-60Hz. Voltage: 3. Equipment included: Yes. Total power: 7.8. Power factor: 0.50. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	7.8 W	LOR	100%
Lamp flux	74 lm	Total flux	74 lm
Luminous efficacy	10 lm/W	Total power	7.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall recessed, Ceiling mounted

Shape and measurements

Length: 6.50 in
Width: 0.12 in
Height: 1.50 in

Adjustability

Fixed

Electric

System power: 7.8 W
Appliance Class: I

Protection

IP: 66
IK: 10