



# Product data sheet

PANEL PERFORMANCE 1200X300 UGR < 19 DALI 30 W 4000 K UGR19  
4058075440630  
LEDVANCE



Rectangular recessed panel luminaires, tool-free installation and low glare, for 1200 x 300 mm ceiling systems with DALI-2 IoT technology. Product features: IoT-ready luminaire with DALI-2 technology. Extruded aluminum frame. Polystyrene diffuser. 3-pole terminal block, cable cross section up to 3 x 2.5 mm². 5-pole terminal block, cable cross section up to 5 x 2.5 mm² (DALI versions). Versions available with CRI 90. Lifetime (L80/B10): up to 60,000 h (at 25 °C). Product benefits: Suitable luminaire for VIVARES and other DALI-2 Light Management Systems. Tool-free electrical connection due to push button connector. Through-wiring possible with included connector box. Energy savings thanks to high system efficacy: up to 120 lm/W. Good glare reduction (UGR < 19). Comfortable light and high color consistency. External driver for extended flexibility and easy installation. Low flicker light thanks to special electronic control gear. 5 years guarantee. Areas of application: Direct replacement for luminaires with fluorescent lamps. Offices, conference rooms. Reception areas, foyers, corridors, elevators. Suitable for recessed ceiling systems with grid size of 300 x 1200 mm. Equipment / Accessories: Accessories for several mounting options available. Connector box with 3-pole or 5-pole terminal included. Security rope for luminaire included. Security brackets included. External control gear included. Not suitable for use with Emergency Conversion Box.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3000 W	CRI	80
Total flux	3600 lm	LOR	100%
Luminous efficacy	1 lm/W	Total power	3000 W

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 4,704.72 in  
Width: 1,161.42 in  
Height: 35.43 in  
Weight: 1700 kg

## Adjustability

Fixed

## Design

Material impression: Aluminum  
Color of housing: White

## Electric

System power: 3000 W  
Appliance Class: II

## Protection

IP: 40  
IK: 03  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: 14...113°F