Product data sheet

ARENA 1200 WHITE WIDE 8980LM 4000K RA>80 DALI 5703821174596

SG ARMATUREN












Arena is an energy efficient surface mounted IP23 luminaire for use in industry and storage. It is easy to install with hinged gear tray, and can be mounted either direct on ceiling (screws) or by using the mounting hooks for horizontal wiring. Arena is available in two lengths and with three different light distributions. Light distribution Direct (Wide) Light technic LED 57W 4000K Ra>80 SDCM 3 L90/B10 >70,000 hrs L80/B20 >100,000 hrs Control/Dimming DALI Protection Class I IP23 IK08 Energy and approvals CE Materials and finish Housing: Sheet steel Colour: White (RAL 9010, 20% gloss) Optics: PMMA Mounting/Connection Suspended or surface, Indoor Cable entry: end caps (knock out) 5 pole screwless terminal block Max. luminaires per circuit breaker: B10: 12, B16: 21, C10: 19, C16: 34

Light output 1



1 x LED
Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

LOR	57 W
Total flu	8980 lm
Total po	158 lm/W
	4000 K
	80

_OR	100%
Γotal flux	8992 lm
Гotal power	57 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 50.00 in Width: 5.45 in Height: 2.35 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 57 W Appliance Class: I

Protection

IP: 23 IK: 08