Product data sheet

URBANO LED 155W 22650LM 4000K IP66 O53 - FOR RESIDENTIAL AREA ROADS REGULATION -15° ... 0° (O50, O51, O52, O..
130195.5L34.1131


LUG



IP 66 IK 09

Professional streetlight luminaire for LED light sources. Mounting: on pillar ø60/76mm, on pillar ø60/48mm (only for luminaires with a degree of regulation 0° ... +15°) - modification .834, on outriggers ø60/76mm, on outriggers ø60/48mm (only for luminaires with a degree of regulation 0° ... +15°) - modification .834 Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.049 m² Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Additional information: Tilt adjustment: 5°, knife switch (for protection class I), access to the driver chamber without the use of tools. The possibility of using one or more power supplies in the luminaire. Additional equipment: luminaire with holder for mounting on a ø60/48mm pillar (only for luminaires with a degree of regulation 0° ... +15°) - index extension: .834 Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting Type of optics: O53 - for residential area roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	155 W	CRI	70
Total flux	22650 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	155 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.74 in
Width: 11.61 in
Height: 5.31 in

Adjustability

Tiltable

Design

Color of housing: Anthracite / graphite

Electric

System power: 155 W
Appliance Class: I

Protection

IP: 66
IK: 09