Product data sheet


TETRIX OBLIQUE 62 IP55 LED DE 2700K MEDIUM BLACK MATT + SNOOT
13512083+1351503X
MODULAR



IP 55


We had a bit of a game in mind when we designed our recessed spot, Tetrix. Playing with pieces, fitting them together in all kinds of intricate ways. Easy to play with, and for everyone. Tetrix invites you to give it your personal touch with design options and accessories. It's versatile, fits everywhere, and is a breeze to install. Tetrix is a new family of recessed downlighters with many possibilities. Compose your Tetrix with a choice of design, installation and accessory.

Light output 1



1 x LED

Nominal lamp power	5 W	LOR	33%
Lamp flux	491 lm	Total flux	160 lm
Luminous efficacy	32 lm/W	Total power	5 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	7.2 W	LOR	33%
Lamp flux	660 lm	Total flux	215 lm
Luminous efficacy	30 lm/W	Total power	7.2 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.62 in
Diameter: 2.44 in

Adjustability

Fixed

Electric

System power: 5-7.2 W

Protection

IP: 55