

Product data sheet

THIMBLE 74 LED DE 3000K MEDIUM SILVER BRONZE BRUSHED ANODISED
11620184
MODULAR




Discrete, curvy & colourful Thimble evokes minimalism, surprise and technology all at once. Subtle curves, slightly revealing colours, high-quality lens and LED. With its deep-recessed and glare-free light source, Thimble’s clean and seamless execution makes it a quiet yet sophisticated choice for high-end residential or hospitality settings. This versatile, elegant architectural downlighter will bring pure form, definition and quality light to any space without stealing all the attention.

Light output 1



1 x LED			
Nominal lamp power	5.7 W	LOR	60%
Lamp flux	730 lm	Total flux	436 lm
Luminous efficacy	77 lm/W	Total power	5.7 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	8.5 W	LOR	60%
Lamp flux	984 lm	Total flux	588 lm
Luminous efficacy	69 lm/W	Total power	8.5 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.35 in
Diameter: 2.91 in
Weight: 0.25 kg

Adjustability

Fixed

Electric

System power: 5.7-8.5 W

Protection

IP: 55