Product data sheet

MINI DADOS ROUND - DN
5421-0-3-980-XX
UNILAMP

Unilamp

IP 65 | IK 08 | ⏚

DADOS an energy saving cube-shaped and cylindrical-shaped compact Led wall light which can be used in both outdoor and indoor environments. Thanks to the robust LM6 aluminium construction and clear tempered glass cover, they protect the luminaire from dust and water and possible harmful impact. It is operated with high power Led with 2700K, 3000K and 4000K color temperature. DADOS is designed to illuminate and make a light effect on the wall. Thanks to a precise Photopia-designed reflector that gives sharp but glare free light distribution. It provides visual guidance in the architectural environment as well as being an eye-catching object. Double layer surface coating is applied thoroughly on the product therefore it is highly corrosion resistant to any extreme environment. • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium reflector. • Weather proof TPE grommet. • Installation work has to be carried on according to the enclosed product manual.

Light output 1

1 x LED

Nominal lamp power	4.6 W	LOR	88%
Lamp flux	530 lm	Total flux	465 lm
Luminous efficacy	115 lm/W	Total power	6.4 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.72 in
Width: 3.96 in
Height: 4.73 in

Adjustability

Fixed

Electric

System power: 6.4 W

Appliance Class: I

Protection

IP: 65
IK: 08