Product data sheet


F-LINE-RT1X115/20ND-SM-300M840
0650580
RIDI



IP 20

Pendant luminaire from the F-LINE product family. Optical control via Louvre, beam pattern symmetric, wide beam, light emission direct/indirect. Lamps R-TUBE not included, Exchange by end customer possible. Housing made of Steel, traffic white, similar to RAL 9016, protection rating IP20. With accessories, the luminaire is suitable for pendant mounting with wire pendant. Wire pendant, length 1.5 metres ZSPT2Z 190 for F-LINE-RT1..., or ZSPT2Z 295 for F-LINE-RT2... to be ordered separately (see accessories). Mains cable, length 1.5 metres with transparent sheath, to be ordered separately (see accessories). Straight, L-shaped, T-shaped and cross-shaped connectors are available for the production of F-LINE constructs. With electronic electrical component On/Off. Replacement by specialist. Rated voltage 220 - 240 V AC/DC 50 - 60 Hz.

Light output 1



1 x LED

Nominal lamp power	21 W	LOR	81%
Lamp flux	2990 lm	Total flux	2413 lm
Luminous efficacy	115 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 49.33 in
Width: 5.91 in
Height: 1.77 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 21 W
Appliance Class: I

Protection

IP: 20