Product data sheet


LUMINAIRE OSLO 650-2 - WITHOUT LOUVERS M6 16LED 2200K
88.02400.0V001
HESS



IP 54


Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium without louvres.

Light output 1




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2651 lm	Total flux	2651 lm
Luminous efficacy	118 lm/W	Total power	22.5 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3964 lm	Total flux	3964 lm
Luminous efficacy	117 lm/W	Total power	33.9 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3710 lm	Total flux	3710 lm
Luminous efficacy	117 lm/W	Total power	31.6 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3453 lm	Total flux	3453 lm
Luminous efficacy	117 lm/W	Total power	29.4 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2923 lm	Total flux	2923 lm
Luminous efficacy	118 lm/W	Total power	24.8 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2374 lm	Total flux	2374 lm
Luminous efficacy	118 lm/W	Total power	20.2 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2087 lm	Total flux	2087 lm
Luminous efficacy	116 lm/W	Total power	18 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1795 lm	Total flux	1795 lm
Luminous efficacy	114 lm/W	Total power	15.7 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1506 lm	Total flux	1506 lm
Luminous efficacy	112 lm/W	Total power	13.4 W
CCT	2200 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1210 lm	Total flux	1210 lm
Luminous efficacy	109 lm/W	Total power	11.1 W
CCT	2200 K		
CRI	80		



1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3189 lm	Total flux	3189 lm
Luminous efficacy	118 lm/W	Total power	27.1 W
CCT	2200 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 25.58 in
Width: 25.58 in
Height: 19.33 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 54