


# Product data sheet

LOUI 50  
925331.0045.1  
RZB




IP  
20

IK  
02

Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Available Colours: white aluminium (RAL 9006) Type of Installation: Pendant Dimensions: L 1121, B 57, H 75 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 4800lm System power: 40W Beam Angle: 104°/107° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 20A Unified Glare Ratio: 23,5 EEC: A++

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 40 W     | CRI         | 80     |
| Total flux         | 4800 lm  | LOR         | 100%   |
| Luminous efficacy  | 120 lm/W | ULOR        | 37%    |
|                    |          | Total power | 40 W   |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 2.24 in  
Width: 44.09 in  
Height: 2.95 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 40 W

## Protection

IP: 20  
IK: 02