# Product data sheet

RECESSED CEILING LUMINAIRE SLASH 2 XHE (EXTREME HIGH EFFICI
2006.3945 - SLASH2 CR613 LED540-840 DIR ELOX ONF
REGENT



IP 20 IK 08

Recessed ceiling luminaire Slash 2 xHE (extreme High Efficiency), with LED, system power: 6.5 W, luminous flux of luminaire 540 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, luminaire profile in aluminium natural-colour anodised with ceiling trim, diffuser in polycarbonate (PC), APD (Added Performance Diffuser), OpalLed, 1 integral control gear, ON/OFF, protection class I, ingress protection IP20, glow wire test 850 °C, impact strength: IK 08 this product contains a light source of energy efficiency class B and EPREL registration number: 1249140 L = 613 mm, B = 61 mm, EL = 602 mm, EB = 48 mm, ET = 70 mm

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 20 W | LOR | 100% |
| Lamp flux | 540 lm | Total flux | 540 lm |
| Luminous efficacy | 27 lm/W | Total power | 6.5 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 24.13 in
Width: 2.40 in
Height: 2.76 in
Weight: 2.88 kg

### Adjustability

Fixed

### Design

Color of housing: Silver gray

### Electric

System power: 6.5 W
Appliance Class: I

### Protection

IP: 20
IK: 08