# Product data sheet

POWERVISION 5 RECESSED LOW BAY LUMINAIRES PW59-GP042-T3-W40

LIGMAN








- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	38 W	CRI	80
Total flux	4569 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	38 W

# Mounting mode

Ceiling mounted

## Shape and measurements

Length: 18.90 in Width: 12.80 in Height: 4.02 in Weight: 6.5 kg

#### Adjustability

Fixed

#### Design

Color of housing: Black, White, Silver gray

# Glare protection

Glare protection: UGR < 19

## Electric

System power: 38 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

#### Protection

IP: 66 IK: 07

Surface temperature: 40°C