



Product data sheet

MAST-MOUNTED LIGHTING CARPO DB M1, 3435LM 23W 740/4000K, ESG, CLEAR, WIDE BEAM, MAST TOP/ATTACHMENT.
9841204469-2920
NORKA



Mastleuchte aus Aluminium mit LED-Bestückung. Einsetzbar in Verkehrsflächen, an Bahnhöfen, Parkplätzen und Straßen mit geringer Durchfahrtsgeschwindigkeit, Masthöhen ca. 6 - 8 m. Leuchtengehäuse aus Aluminium, pulverbeschichtet in DB703. Einsetzbar im Innen- und Außenbereich gemäß Schutzart IP 66, Schutzklasse II, Schlagfestigkeit IK08. Abschlusscheibe aus Einscheiben-Sicherheitsglas, glasklar, mit innenliegender Linsenoptik. Eingebautes DALI-Betriebsgerät, Versorgungsspannung 230 V AC/DC. 10 kV Transientenfilter.HINWEISGelistet: DB InfraGO Personenbahnhöfe - Gruppe 10. Weight: 6,7 kg; Light sensor: NO; Version: m1; Lamp service life: L80 B10 > 60,000 h at +45°C; Extreme-temperature: -25°C to +45°C; Housing material: Aluminium; Colour housing: DB703, powder coated; Material / Cover: ESG, clear; Light distribution: wide beam; ENEC / VDE: YES / NO; Lamp power: 32 W; max. System power: 23 W; Colour temperature: White, 740/4000 K, Ra > 70; Protection class: II; IP-rating: IP66; Type of gear: LED operating device current-controlled, DALI (additional 2 x 1.5 mm² control line), 220 V - 240 V AC; Through-wiring: without; Usage: railway platforms/stations; Impact strength: IK08; Transient protection: 10 kV;

Light output 1



1 x LED			
Nominal lamp power	23 W	LOR	96%
Lamp flux	3435 lm	Total flux	3284 lm
Luminous efficacy	149 lm/W	Total power	23 W
CCT	4000 K		
CRI	74		

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 21.57 in
Width: 9.45 in
Height: 7.60 in

Adjustability

Tiltable

Design

Material impression: Aluminum

Electric

System power: 23 W
Appliance Class: II

Protection

IP: 66
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -13...113°F