

Product data sheet

PRO-VISON MIDI, 40LEDS OPTIEK 3


41344X2X

PROLUMIA




Light Source: Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium FP programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1




1 x LED

Nominal lamp power	48.3 W	LOR	100%
Lamp flux	6400 lm	Total flux	6400 lm
Luminous efficacy	133 lm/W	Total power	48.3 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	43.8 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	132 lm/W	Total power	43.8 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	46.2 W	LOR	100%
Lamp flux	5800 lm	Total flux	5800 lm
Luminous efficacy	126 lm/W	Total power	46.2 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	54.2 W	LOR	100%
Lamp flux	6800 lm	Total flux	6800 lm
Luminous efficacy	125 lm/W	Total power	54.2 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	51 W	LOR	100%
Lamp flux	6400 lm	Total flux	6400 lm
Luminous efficacy	125 lm/W	Total power	51 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	54.4 W	LOR	100%
Lamp flux	7200 lm	Total flux	7200 lm
Luminous efficacy	132 lm/W	Total power	54.4 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	57.4 W	LOR	100%
Lamp flux	7200 lm	Total flux	7200 lm
Luminous efficacy	125 lm/W	Total power	57.4 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	51.3 W	LOR	100%
Lamp flux	6800 lm	Total flux	6800 lm
Luminous efficacy	133 lm/W	Total power	51.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 23.62 in

Width: 12.40 in

Height: 5.31 in

Electric

System power: 43.8-57.4 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE