Product data sheet

CALABRONET
40033/NE
MARTINELLI LUCE



IP 20

Combinable swivel system, direct/indirect diffused light. Composed of two length of aluminium tubular profiles (70cm - 160cm) connected togheter with a particular joint (40032/NE) for differents configurations. Module with spots for light source LED integrated and electronic driver insered into the stud, to be fixed on the ceiling or false ceiling for two contiguous modules. Variation for G5 T5 8W/20W tube LED (40030/NE - 40031/NE) and ceiling stud for three profiles, to be fixed on the ceiling.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	618 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	9 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	618 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	9 W

Mounting mode

Pendant

Shape and measurements

Length: 27.56 in
Width: 1.77 in
Height: 1.77 in
Weight: 1.3 kg

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 20

Design

Color of housing: Black

Designer: Emiliana Martinelli