


Product data sheet

TYP L54 PC 5S LE3
TYPHON EMERGENCY
DEXTRA




Typhon - 1500mm Single, IP65 Surface mounted moisture resistant luminaire. GRP body, polycarbonate diffuser. Complete with tooled access Stainless steel diffuser retaining clips. Options: LE3 - Lithium Emergency (421 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Reacta 44 Daylight and Presence Detection Sensor R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* RLS - Reacta-Link Wireless Presence RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode* *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.7 W	CRI	80
Total flux	4644 lm	LOR	100%
Luminous efficacy	146 lm/W	ULOR	4%
		Total power	31.7 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	84
Total flux	421 lm	LOR	100%
Luminous efficacy	140 lm/W	ULOR	4%
		Total power	3 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 61.69 in

Width: 4.25 in

Height: 4.13 in

Electric

System power: 34.7 W

Ballast: ECG

Controller: DALI

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 65

Designation labels: CE