


Product data sheet

MULTILUME SLIM DELTA VTB 600X600 RA 90 4000K CLO WAGO WINSTA
23216-529
FAGERHULT



Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. For suspended ceilings with visible T-bars (15 or 24 mm). Do not cover with insulation. For detailed information, see the installation instructions on our website. Connection Connection in separate ballast box.Snap-in terminal block 3x2,5mm2 (x2), through-wiring possible. 5x2,5mm2 (x2) when dimming. Can also be supplied with earthed mains cable and plug. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Delta – microprism louvre in UV stabil polystyrene. Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	32 W	CRI	90
Total flux	3638 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	32 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 0.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 32 W

Protection

IP: 44