

# Product data sheet

PAULA VII  
9.647.3066.05  
LEIPZIGER LEUCHTEN



IP  
55

Recommended mounting height 4.50 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711  
Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 125 W   |
| Lamp flux          | 6800 lm |
| Luminous efficacy  | 41 lm/W |
| CCT                | 3400 K  |
| CRI                | 54      |

|             |         |
|-------------|---------|
| LOR         | 83%     |
| Total flux  | 5651 lm |
| Total power | 137 W   |



### 1 x High pressure mercury vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 80 W    |
| Lamp flux          | 4000 lm |
| Luminous efficacy  | 37 lm/W |
| CCT                | 3400 K  |
| CRI                | 54      |

|             |         |
|-------------|---------|
| LOR         | 83%     |
| Total flux  | 3324 lm |
| Total power | 89 W    |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 28.74 in

Diameter: 28.74 in

## Electric

System power: 89-137 W

## Protection

IP: 55