



# Product data sheet

K-1 89 GU10  
102749XX  
MODULAR




Decorative simplicity Every project needs a basic spotlight for general lighting. K is our suggestion for those who like to keep things simple. Available with a diameter of 80 or 89 mm, a flat or sloping edge and in aluminium or with a white or black structure, K integrates easily into any room. Choose the directional model for a greater interplay of light.


## Light output 1




<b>1 x LED</b>			
Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	350 lm	LOR	99%
Luminous efficacy	58 lm/W	Total flux	346 lm
CCT	2700 K	Total power	6 W
CRI	80		



<b>1 x LED</b>			
Nominal lamp power	5.5 W	Socket	Gu10
Lamp flux	389 lm	LOR	98%
Luminous efficacy	63 lm/W	Total flux	380 lm
CCT	2700 K	Total power	6 W
CRI	80		




<b>1 x Halogen low voltage lamp without reflector</b>			
Nominal lamp power	50 W	LOR	100%
Lamp flux	410 lm	Total flux	410 lm
Luminous efficacy	8 lm/W	Total power	50 W
CCT	2800 K		
CRI	100		



**1 x Halogen low voltage lamp without reflector**

Nominal lamp power	35 W	LOR	99%
Lamp flux	375 lm	Total flux	372 lm
Luminous efficacy	11 lm/W	Total power	35 W
CCT	2800 K		
CRI	100		



**1 x Halogen low voltage lamp without reflector**

Nominal lamp power	50 W	LOR	99%
Lamp flux	404 lm	Total flux	399 lm
Luminous efficacy	8 lm/W	Total power	50 W
CCT	2800 K		
CRI	100		

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Height: 0.39 in

Diameter: 3.54 in

**Adjustability**

Rotatable, Tiltable

**Electric**

System power: 6-50 W

Appliance Class: I

**Protection**

IP: 20

IK: 01