


# Product data sheet

LIGHT LINEAR DENVER 2 STREET AND AREA LUMINAIRES  
DE-20011-T3-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 100 km/h - Surge protection 10kV

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.5 W	CRI	80
Total flux	5893 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	53.5 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.5 W	CRI	80
Total flux	5893 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	53.5 W

## Mounting mode

Standing / Bollard, Pole top mounted

## Shape and measurements

Length: 84.65 in  
Width: 5.91 in  
Height: 3.54 in  
Weight: 31.3 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 107 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C