



# Product data sheet

FLAT POLYMER0  
311946.002.4.19  
RZB



Series: FLAT POLYMER0 Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. Functional parameters of a master luminaire (ceiling height of approx. 2.8m): HF detector 24GHz with integrated corridor function. Coverage: approx. 130° radial. Easy adjustment of functions via associated push button switches. Sensitivity/Range: 0.5-5m radial, adjustable from 10-100%. Time control 1second to 15minutes in 8different levels. Daylight detection with 5brightness levels and learning mode. Up to 9slave luminaires can be operated with one master luminaire (max. up to 150W / 230W). Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: white Diameter: 360mm Height: 100mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 19W Rated luminous flux: 2000lm Luminous efficiency: 105lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP40

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 19 W     | CRI         | 80     |
| Total flux         | 2000 lm  | LOR         | 100%   |
| Luminous efficacy  | 105 lm/W | ULOR        | 11%    |
|                    |          | Total power | 19 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.94 in  
Diameter: 14.17 in

## Adjustability

Fixed

## Electric

System power: 19 W

## Protection

IP: 40  
IK: 10