


Product data sheet

HOME 601
312182.002.1.76
RZB



Series: Home 601 Type of Protection: IP 40 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Frame: white powder coated aluminium. Diffuser: plastic (PMMA) opal, diffuser and light guide made of non-yellowing PMMA, lateral light emission with LED, lamp (LED) included, external converter (height 32mm). Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 622, B 622, Lamp: LED Life time: 50000 h Colour Temperature: 4000K Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 3550lm System power: 37W Beam Angle: 120°/113° Inrush current: 20,4A Unified Glare Ratio: 21,4 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	37 W	CRI	80
Total flux	3550 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	37 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 24.49 in
Width: 24.49 in
Height: 1.77 in

Adjustability

Fixed

Electric

System power: 37 W

Protection

IP: 40