# Product data sheet


EP 145 LED 24L35 BP SC 740 RS/MSU
96269153
THORN LIGHTING



IP 66 IK 08

A 19th Century styled suspended lantern with 24 LEDs driven at 350mA with Street & Comfort optic. Integral power reduction function which dims down to 50% power, effective 3 hours before and 5 hours after a calculated midnight. Class II electrical, IP66, IK08. Body: stainless steel, painted black (close to RAL9005). Canopy: GRP/Polyester, black (close to RAL9005) finish. Enclosure: 5mm thick tempered glass. Complete with 4000K LED Dimensions: 420 x 420 x 944 mm Total power: 26 W Weight: 10.3 kg Scx: 0.145 m²

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 26 W | CRI | 70 |
| Total flux | 2182 lm | LOR | 100% |
| Luminous efficacy | 84 lm/W | Total power | 26 W |

### Mounting mode

Pendant

### Shape and measurements

Length: 16.54 in
Width: 16.54 in
Height: 37.17 in
Weight: 10.3 kg

### Design

Material impression: Stainless steel
Color of housing: Black

### Electric

System power: 26 W
Voltage: 230 V AC
Appliance Class: II

### Protection

IP: 66
IK: 08
Designation labels: CE