Product data sheet


EXIT 90-3209-60-0U LEDSC4





LedsC4 Exit 90-3209-60-OUV1 Ceiling fixture for indoor use. For downlighting. Structure material: Aluminium. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 2.3 Product width or diameter (mm): 180 Product height (mm): 205 Class 2. IP: IP23. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 25.9W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 2. Hours of life: 50.000h L80B20. UGR: 17.8. Photobiological risk: RG1. Real flux (lm): 2284. Nominal flux (lm): 2666. Real lm/W: 85. Voltage / frequency range: 100-240/50-60Hz. Voltage: 36. Equipment included: Yes. Multi-voltage equipment included. Total power: 26.9. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI

26 W 2284 lm 88 lm/W 4000 K 80

LOR Total flux Total power

99%
2264 lm
26 W

Mounting mode

Ceiling mounted, Wall recessed

Shape and measurements

Length: 7.09 in Width: 7.09 in Height: 8.07 in

Adjustability

Fixed

Electric

System power: 26 W Appliance Class: II

Protection

IP: 23