

Product data sheet

UTA (BEADED)
9.860.2052.06
LEIPZIGER LEUCHTEN



Mounting height 4.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in color - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL-or DB -color without surcharge - Scope of supply includes hot galvanized and painted offset pole dia. 76 mm, and bracket.

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	100 W	LOR	78%
Lamp flux	10400 lm	Total flux	8109 lm
Luminous efficacy	71 lm/W	Total power	115 W
CCT	2000 K		
CRI	25		

Mounting mode

Pole integrated, Ceiling mounted

Shape and measurements

Height: 27.17 in
Diameter: 23.62 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 115 W
Ballast: ECG

Protection

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F