Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-7LN02-04L05-6515050 LIF LINE 1X6 150W 5000K 120°
VARTON



IP 65

A light weight and hight efficiency industrial luminaire mounted on a bracket with swichable angle. Construction: modular body made of aluminum, mounting elements made of steel. Optics made of acrylic. Installation: an overlay on the surface using a rotary lyre. Tilt angle adjustment from -60 to +60 degrees in 30 degree increments. The convenience of connecting to the power supply via a cable removed from the lamp, without disassembling the lamp body. Application: for lighting warehouses with inter-stack and pallet storage. Input voltage (AC, 50Hz): 120...277 AC frequency: 50 Input voltage (DC): - Flicker: 5 Climatic modification and category of placement: УХЛ2 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK10 Power factor: 0,95 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/lif/lif-line-1x6/svetodiodnyy-svetilnik-varton-promyshlennyy-lif-150-vt-5000-k-klass-zashchity-ip65-ugol-120-gradusov_1/

Light output 1



1 x LED

Nominal lamp power	150 W	LOR	100%
Lamp flux	24300 lm	Total flux	24302 lm
Luminous efficacy	162 lm/W	Total power	150 W
CCT	5000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 53.35 in
Width: 3.39 in
Height: 6.50 in

Adjustability

Fixed

Electric

System power: 150 W

Protection

IP: 65